



BASIC SEAT

DESCRIPTION

Seat on pads

Seat bottom height : 470 - 610 mm

Back height : 430 mm

Weight : 14 kg

Volume : 0.18 m³

Removable padding

Backrest height adjustment

Steel base

Certified total ESD reliability according to EN 61340-5-1



ELECTRICAL SPECIFICATIONS

Resistance : Rgp = < 10⁵ Ohm / Rg < 10⁷ Ohm

Permanent contact backrest:

REFERENCES	CHARACTERISTICS
02-0401-Eg150-S	Vinyl
02-0401-Eg150-TB	Blue
02-0401-Eg150-TG	Grey
02-0401-Eg150-TN	Black
02-0401-Eg150-TR	Red



Backrest with permanent contact and seat tilt:

REFERENCES	CHARACTERISTICS
02-0401-Eg154-S	Vinyl
02-0401-Eg154-TB	Blue
02-0401-Eg154-TG	Grey
02-0401-Eg154-TN	Black
02-0401-Eg154-TR	Red

Synchronous system with voltage adjustment:

REFERENCES	CHARACTERISTICS
02-0401-Eg157-S	Vinyl
02-0401-Eg157-TB	Blue
02-0401-Eg157-TG	Grey
02-0401-Eg157-TN	Black
02-0401-Eg157-TR	Red

COVERING

Vinyle	Tissu Bleu	Tissu Gris	Tissu Noir	Tissu Rouge
				



DESCRIPTION

Seat on pads and running boards

Seat height 620-870 mm

Back height: 430 mm

Weight: 17.5 kg

Volume: 0.18 m³

Removable padding

Backrest height adjustment

Steel base

Certified total ESD reliability according to EN 61340-5-1

ELECTRICAL SPECIFICATIONS

Resistance : Rgp = < 10⁵ Ohm / Rg < 10⁷ Ohm



Permanent contact backrest:

REFERENCES	CHARACTERISTICS
02-0401-E9152-S	Vinyl
02-0401-E9152-TB	Blue
02-0401-E9152-TG	Grey
02-0401-E9152-TN	Black
02-0401-E9152-TR	Red


Backrest with permanent contact and seat tilt:

REFERENCES	CHARACTERISTICS
02-0401-E9156-S	Vinyl
02-0401-E9156-TB	Blue
02-0401-E9156-TG	Grey
02-0401-E9156-TN	Black
02-0401-E9156-TR	Red

Synchronous system with voltage adjustment:

REFERENCES	CHARACTERISTICS
02-0401-E9159-S	Vinyl
02-0401-E9159-TB	Blue
02-0401-E9159-TG	Grey
02-0401-E9159-TN	Black
02-0401-E9159-TR	Red

COVERING

Vinyle	Tissu Bleu	Tissu Gris	Tissu Noir	Tissu Rouge
				



DESCRIPTION

Seat on castors

Seat height 470 - 610 mm

Back height: 430 mm

Weight: 14.5 kg

Volume: 0.18 m³

Removable padding

Ergonomic Package: Adjusting tension, adjusting seat depth, adjusting seat tilt and adjusting backrest height

Aluminum base

Certified total ESD reliability according to EN 61340-5-1



ELECTRICAL SPECIFICATIONS

Resistance : $R_{gp} = < 10^5 \text{ Ohm}$ / $R_g < 10^7 \text{ Ohm}$

Permanent contact backrest:

REFERENCES	CHARACTERISTICS
02-0401-E9151-S	Vinyl
02-0401-E9151-TB	Blue
02-0401-E9151-TG	Grey
02-0401-E9151-TN	Black
02-0401-E9151-TR	Red

Backrest with permanent contact and seat tilt:

REFERENCES	CHARACTERISTICS
02-0401-E9155-S	Vinyl
02-0401-E9155-TB	Blue
02-0401-E9155-TG	Grey
02-0401-E9155-TN	Black
02-0401-E9155-TR	Red

Synchronous system with voltage adjustment:

REFERENCES	CHARACTERISTICS
02-0401-E9158-S	Vinyl
02-0401-E9158-TB	Blue
02-0401-E9158-TG	Grey
02-0401-E9158-TN	Black
02-0401-E9158-TR	Red

COVERING

Vinyle	Tissu Bleu	Tissu Gris	Tissu Noir	Tissu Rouge
			