



NEXXIT SEAT

DESCRIPTION

On pads

Synchronous system with automatic tension adjustment

Seat height 470 - 620 mm

Ergonomic package:

- Adjusting the seat depth
- Adjusting the seat tilt
- Settings in file height

Steel base

Certified total reliability ESD according to EN 61340-5-1




ELECTRICAL SPECIFICATIONS


Resistance : $R_{gp} = < 10^5 \text{ Ohm}$ / $R_g < 10^7 \text{ Ohm}$

REFERENCES	CHARACTERISTICS
02-0401-Eg030/PU	PU
02-0401-Eg030/S	Supertec
02-0401-Eg030/N	Black fabric
02-0401-Eg030	Vinyl


Fabric



Vinyl



Foam (PU)



Supertec





DESCRIPTION

On pads with running boards

Synchronous system with automatic tension adjustment

Seat height 580 - 630 mm

Ergonomic package:

- Adjusting the seat depth
- Adjusting the seat tilt
- Settings in file height

Steel base


Certified total ESD reliability according to EN 61340-5-1

ELECTRICAL SPECIFICATIONS

Resistance : $R_{gp} = < 10^5 \text{ Ohm}$ / $R_g < 10^7 \text{ Ohm}$



REFERENCES	CHARACTERISTICS
02-0401-Eg031/PU	PU
02-0401-Eg031/S	Supertec
02-0401-Eg031/N	Black fabric
02-0401-Eg031	Vinyl

Fabric	Vinyl	Foam (PU)	Supertec
			



DESCRIPTION

On castors

Synchronous system with automatic tension adjustment

Seat height 450 - 580 mm

Ergonomic package:

- Adjusting the seat depth
- Adjusting the seat tilt
- Settings in file height

Steel base

Certified total ESD reliability according to EN 61340-5-1

ELECTRICAL SPECIFICATIONS

Resistance : $R_{gp} = < 10^5 \text{ Ohm}$ / $R_g < 10^7 \text{ Ohm}$



REFERENCES	CHARACTERISTICS
02-0401-Eg033/PU	PU
02-0401-Eg033/S	Supertec
02-0401-Eg033/N	Black fabric
02-0401-Eg033	Vinyl

Fabric	Vinyl	Foam (PU)	Supertec
	