



NEON SEAT

DESCRIPTION

Seat on skates (without cushion)

Seat height: 450 - 620 mm

Back height: 570 mm

Weight: 21 kg

Volume: 0.25 m3

Removable padding

Ergonomic pack:

- Voltage adjustment
- Adjusting the seat depth
- Adjusting the seat tilt
- Backrest height adjustment

Aluminum base

ESD certified according to EN 61340-5-1

Other heights on request



ELECTRICAL SPECIFICATION

Resistance : $R_{gp} = < 10^5 \text{ Ohm}$ / $R_g < 10^7 \text{ Ohm}$

REFERENCES	CHARACTERISTICS
02-0401-Eg560	Permanent contact - H= of seat 450 – 620 mm
02-0401-Eg570	Synchronous system - H= of seat 450 – 620 mm

DESCRIPTION

Seat on skates with running board (without cushion)

Seat height: 590 - 870 mm

Back height: 570 mm

Weight: 24 kg

Volume: 0.25 m3

Removable padding

Ergonomic pack:

- Voltage adjustment
- Adjusting the seat depth
- Adjusting the seat tilt
- Backrest height adjustment

Aluminum base

ESD certified according to EN 61340-5-1



ELECTRICAL SPECIFICATION

Resistance : $R_{gp} = < 10^5 \text{ Ohm}$ / $R_g < 10^7 \text{ Ohm}$

REFERENCES	CHARACTERISTICS
02-0401-Eg561	Permanent contact - H= of seat 590 – 870 mm
02-0401-Eg571	Synchronous system - H= of seat 590 – 870 mm



DESCRIPTION

Seat on castors (with cushion)

Seat height 450 - 620 mm

Back height: 570 mm

Weight: 21 kg

Volume: 0.25 m³

Removable padding

Ergonomic pack:

- Voltage adjustment
- Adjusting the seat depth
- Adjusting the seat tilt
- Backrest height adjustment

Aluminum base

ESD certified according to EN 61340-5-1



ELECTRICAL SPECIFICATION

Resistance : Rgp = < 10⁵ Ohm / Rg < 10⁷ Ohm

REFERENCES	CHARACTERISTICS
02-0401-E9563	Permanent contact - H= 450 - 620 mm
02-0401-E9573	Synchronous system - H= 450 - 620 mm

CUSHIONS (Seat bottom & backrest)

FABRICS	VINYL	POLYURETHANE FOAM	SUPERTEC
02-0401-9588E/B Blue 	02-0401-9588E/C Black 	02-0401-9588E-PU Black 	02-0401-9588E/S Black 
02-0401-9588E/G Grey 			
02-0401-9588E/N Black 			



EDGINGS COLORS TO CHOOSE :



Orange



Grey



Vert



Blue

*Add to the end of references the desired color. Example : 02-0401-E9560-**O** for the **Orange***