



EURO BOX CARTS 600 x 400 mm

DESCRIPTION

Welded assembly

Dissipative gray epoxy coating RAL 7015

2 swivel ESD wheels with brakes + 2 fixed ESD wheels with tire

Ball bearing hub

9380 | 9390 :

- 3 levels adjustable in 50 mm increments
- Capacity 1 bin 600 x 400 mm per level
- Inclination of 15° or 30°
- Load per tray : 80 kg

9383 :

- 5 levels adjustable in 100 mm increments
- Capacity : 3 boxes 600 x 400 mm per level
- Inclination of 15° or 30°
- Load per tray : 80 kg



9380

ELECTRICAL SPECIFICATIONS

Surface resistivity : $<10^7 \Omega$

In compliance with the norm : IEC 61340

References	Charge (kg)	Ø wheels (mm)	Useful dimensions tray L x W (mm)	External dimensions L x W x H (mm)	Loading heights (mm)	Weight (kg)
08-0509-09380	250	125	410 x 610	525 x 666 x 1101	238 / 538 / 838	31
08-0509-09390	250	125	820 x 610	935 x 666 x 1101	238 / 538 / 838	38
08-0509-09383	300	160	1240 x 610	1372 x 685 x 1686	298 / 598 / 898 / 1198 / 1498	73



9390



9383

