



TABLE TOP CARTS FOR BOX

DESCRIPTION

Electric static discharge construction (ESD = Electrostatic Discharge)

Tubular steel and sectional steel welded, conductive powder coating, slate grey RAL 7015

Hubs with precision deep groove ball bearing

3 frame shelves in 1 euro box (600 x 400 mm each one)

2 swivel castors with brakes + 2 fixed-wheel

9381 | 9391 :

- 3 levels ajustable in 50 increments
- Capacity : 1 bin 600 x 400 mm per level
- Inclination of 15° or 30°
- Cargo per tray : 80 kg

9383 :

- 5 levels ajustable in 100 increments
- Capacité : 3 bin 600 x 400 mm per level
- Inclination of 15° or 30°
- Cargo per tray : 80 kg



ELECTRONIC CHARACTERISTICS

Surface resistivity : $<10^7 \Omega$

In accordance with the norm IEC 61340

Références	Cargo (kg)	Ø Wheels (mm)	Tray dimensions L x l (mm)	External dimensions L x l x H (mm)	Height (mm)	Weight (kg)
08-0509-09381	250	125	410 x 610	525 x 666 x 1101	257 / 557 / 857	41
08-0509-09391	250	125	820 x 610	935 x 666 x 1101	257 / 557 / 857	55
08-0509-09384	300	160	1240 x 610	1372 x 685 x 1686	317 / 617 / 917 / 1217 / 1517	123

