



TABLE TOP CARTS

DESCRIPTION

Electric static discharge construction
 Tubular steel and sectional steel welded,
 conductive powder coating, slate grey
 Screw and plug type construction
 2 swivel and 2 fixed-wheel castors
 Hubs with precision deep groove ball bearing
 Maximum comfort : Very low starting, rolling and swivelling resistance
 Low noise operation on level floors, tyres are non-marking
 Capacity of upper box : 80kg

ELECTRICAL CHARACTERISTICS

Surface resistivity : $<10^7 \Omega$
 In conformity with the standard IEC 61340



Références	Cargo (kg)	Ø Wheels (mm)	Tray dimensions L x l (mm)	Outer dimensions L x l x H (mm)	Number of tray	Tray Heights (mm)	Weight (kg)
08-0509-01860	300	125	850 x 500	980 x 509 x 1020	2	206 / 827	28
08-0509-01861	300	125	1000 x 600	1130 x 609 x 1020	2	206 / 827	35
08-0509-01870	300	125	850 x 500	980 x 509 x 1020	2	206 / 517 / 827	29
08-0509-01871	300	125	1000 x 600	1130 x 609 x 1020	2	206 / 517 / 827	37
08-0509-01880	300	125	850 x 500	980 x 509 x 1020	3	206 / 514 / 826	38
08-0509-01881	300	125	1000 x 600	1130 x 609 x 1020	3	206 / 514 / 826	47

1870
1871

