



CART WITH HANDLE

DESCRIPTION

Welded assembly
 Dissipative gray epoxy coating RAL 7015
 Dissipative trays
 2 swivel ESD wheels with brakes and 2 fixed ESD wheels with tire
 Ball bearing hub
 Low noise displacement on flat floors, non-tracing bandage
 Maximum load per shelf: 50 kg
 Ability to add additional shelves



ELECTRICAL SPECIFICATIONS

Surface resistivity : $<10^7 \Omega$
 In compliance with the norm : IEC 61340

Reference	Charge (kg)	Ø Wheels (mm)	Useful dimensions trays L x W (mm)	External dimensions L x W x H (mm)	Trays number	Trays heights (mm)	Weight (kg)
08-0509-09100	500	160	850 x 500	1019 x 509 x 1111	3	235 / 635 / 1035	41
08-0509-09101	600	200	1000 x 600	1169 x 609 x 1152	3	276 / 676 / 1076	54
08-0509-09200	500	160	850 x 500	1019 x 509 x 1511	4	235 / 635 / 1035 / 1435	47
08-0509-09201	600	200	1000 x 600	1169 x 609 x 1552	4	276 / 676 / 1076 / 1476	62
08-0509-09301	600	200	1000 x 600	1169 x 609 x 1800	4	276 / 676 / 1076 / 1476	66
08-0509-09302	600	200	1000 x 700	1169 x 709 x 1800	4	276 / 676 / 1076 / 1476	73
08-0509-09303	600	200	1200 x 800	1369 x 809 x 1800	4	276 / 676 / 1076 / 1476	106
08-0509-09341	600	200	1000 x 600	1169 x 609 x 1800	5	276 / 576 / 876 / 1176 / 1476	72
08-0509-09342	600	200	1000 x 700	1169 x 709 x 1800	5	276 / 576 / 876 / 1176 / 1476	84
08-0509-09343	600	200	1200 x 800	1369 x 809 x 1800	5	276 / 576 / 876 / 1176 / 1476	121

