



## 01-0402-32190

### DESCRIPTION

Size from 36 to 48  
 Microfiber with breathable textile inlays, grey/blue  
 Mesh lining  
 Instep area with lacing  
 Shock absorbant  
 PU midsole  
 Slip resistance PU outsole sole  
 Steel toe cap  
 Metalfree penetration resistance  
 Replaceable acc Wave insole (article no. 3580)  
 Sanitized treated  
 ESD dissipative according to DIN EN 61340  
 In compliance with the norms : CE, EN ISO 20345:2011, S1P, SRC



REFERENCE	MODEL
01-0402-32190-XX	Blue





## SEMELLE D'USURE

- 1\_ ESD compatible selon DIN EN 61340
- 2\_ SRC-antidérapant selon EN ISO 20345:2011
- 3\_ Profil autonettoyant
- 4\_ Talon asymétrique pour un positionnement naturel du pied
- 5\_ Torsion en TPU
- 6\_ Protection de flexion (grande stabilité latérale)
- 7\_ Résistance au carburant



3580

Pointure 36-52 (fermé)




3582

Pointure 36-52 (ouvert)



TALON ASYMETRIQUE



Embout acier

**S1P**

SEMELLE ANTIPERFORATION  
NON-MÉTALLIQUE

