

**01-0402-32243****DESCRIPTION**

Pointure du 36 au 48  
Smooth leather with breathable textile inlays, black in ATEX design  
Breathable lining with Silver ions  
Instep area with lacing  
Shock absorbant  
PU midsole  
Slip resistance  
PU outsole sole  
Steel toe cap  
Metalfree penetration resistance  
Replaceable acc Wave insole (article no. 3580)  
Sanitized treated  
ESD dissipative according to DIN EN 61340  
Reflective material  
Conforme aux normes : CE, EN ISO 20345:2011, S1P, SRC

REFERENCE	MODEL
01-0402-32243-XX	Black





## SEMELLE D'USURE

- 1\_ESD compatible selon DIN EN 61340
- 2\_SRC-antidérapant selon EN ISO 20345:2011
- 3\_Profil autonettoyant
- 4\_Talon asymétrique pour un positionnement naturel du pied
- 5\_Torsion en TPU
- 6\_Protection de flexion (grande stabilité latérale)
- 7\_Résistance au carburant



3580

Pointure 36-52 (fermé)



3582

Pointure 36-52 (ouvert)



TALON ASYMETRIQUE



Embout acier

**S1P**

SEMELLE ANTIPERFORATION  
NON-MÉTALLIQUE

