01-0402-34252

DESCRIPTION

Size from 36 to 48
Smooth leather, grey/yellow
Breathable lining with Silver ions
Instep area with lacing
Foamed PU midsole
Slip resistance
TPU outsole sole
Steel toe cap
Metalfree penetration resistance
Replaceable acc
Wave insole (article no. 3577)
Sanitized treated
ESD dissipative according to DIN EN 61340
Scratch-resistant coating in heel and toe area
In compliance with the norms : CE, EN ISO 20345:2011, S3, SRC

REFERENCE	MODEL
01-0402-34252-XX	Yellow

PROMATEC
votre partenaire en protection ESD
TÉL +33 (0)4 90 02 38 10 I FAX +33 (0)4 90 02 37 69 I
EMAIL info@promatec-france.com I WEB www.promatec-france.com
ESD

SEMELLE D'USURE

1_ESD compatible selon DIN EN 61340
2_SRC-antidérapant selon EN ISO 20345:2011
3_Zone de flexion optimisent le déroulement
4_Haute résistance à l'abrasion
5_Ammortissement confortable et haute flexibilité
6_Insert anti-torsion

TALON ASYMÉTRIQUE

PROMATEC
votre partenaire en protection ESD
TÉL +33 (0)4 90 02 38 10 I FAX +33 (0)4 90 02 37 69 I
EMAIL info@promatec-france.com I WEB www.promatec-france.com

ESD